

ST-15 2-Shaft Shredder

The ST-15 reduces data tapes, books, confidential documents and other materials to a secure shred size, providing you with higher security.

It does more so you can DO MORE!

STANDARD FEATURES

CUTTING CHAMBER

The ST-15 shredder features Shred-Tech's cast aluminum shredder body with patent pending "cast-in" steel cleaning fingers.

DRIVE SYSTEM

The ST-15 shredder is equipped with a 30 HP electric gear reduced motor for 60 HZ and 25 HP for 50 HZ.

KNIVES

Shred-Tech Engineers have designed each knife profile and configuration to maximize throughput, while maintaining a confidential shred size.

CONTROL PANEL

The ST-15 control panel, designed by certified Shred-Tech technicians, features illuminated function buttons, keyed power switch, fused lockable disconnect, hour meter and a programmable logic controller for shredder functions, including knife reversal on overload.

HOPPER AND STANDS

Quality is evident in the workmanship of Shred-Tech's extra heavy duty stand and hopper. As an option, the stand and hopper can be modified to suit the application or installation.

HEX SHAFTS

The unique design of the machined hex shafts maximizes knife placement options and allows for easy knife removal and machine maintenance. Size for size, the hex shaft is several times stronger than a keyed shaft. The Shred-Tech hex shaft drive system offers the highest knife tip cutting force of any comparable shredder on the market.





ST-15

2-Shaft Shredder

The ST-15 reduces confidential documents to a secure shred size, providing you with higher security.

| SHREDDER TECHNICAL SPECIFICATIONS | | ST-15 |
|---|--|-----------|
| MEASUREMENTS | | |
| M/C Length | | 58" |
| M/C Width | | 40" |
| M/C Height | | 90" |
| M/C Weight | | 1,350 lbs |
| Floor Space (sq.ft.) | | 16 |
| PRODUCT SPECIFICATIONS | | |
| Drive | | Electric |
| Number of Motors | | 1 |
| Horsepower | | 25/30 HP |
| Voltage | | 208-600 |
| Hertz | | 50/60 |
| Knife Thickness (STD) | | 5/8" |
| Number of Knives | | 32 |
| Knife Diameter | | 6 3/4" |
| Hex Size | | 2 11/16" |
| Distance Between Shafts | | 5 7/8" |
| Cutting Chamber | | 13" x 21" |
| Discharge Height | | 40" |
| Hopper Height | | 38" |
| Hopper Opening | | 22" x 28" |
| Stand Opening | | 30" |
| Stand Opening | | 38" |
| OPTIONAL FEATURES | | |
| PLC Interfacing for Peripheral Equipment | | |
| Custom Stands and Hoppers | | |
| Feed and Discharge Conveyors | | |
| Truck Mounted | | |
| Airveeying Discharge | | |
| Magnetic Ferrous Separation | | |
| MAINTENANCE | | |
| Several design refinements proven successful to increase ease of maintenance and shredder durability in Shred-Tech's model line up have been incorporated into the ST-15 shredder. Bulkhead walls at either end of the cutting chamber provide excellent bearing and seal protection. The modular light-weight cast construction facilitates quick and easy assembly. | | |

Product specifications subject to change without notice.

>> All Shred-Tech Shredders are available under US Federal Supply Contract.® All rights reserved. Shred-Tech and Shred-Tech logo are registered trade-marks of Shred-Tech.

>> SHRED-TECH. COMPLETE INFORMATION DESTRUCTION AND RECYCLING SOLUTIONS.

W www.shred-tech.com | E shred@shred-tech.com | T 800.465.3214 or 519.621.3560 | F 519.621.4288
SERVICE HOTLINE 877.566.2345

